

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : FMI RC-21

1.2. Recommended use and restrictions on use

Recommended use : Silicone release coating

1.3. Supplier

FMI Chemical, Inc.
4 Northwood Drive
Bloomfield, CT 06002
United States
T 860-243-3222

1.4. Emergency telephone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)
CCN 201349
Back-up Emergency Number: 703-741-5970 (D.C, USA)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	Causes skin irritation
Reproductive toxicity Category 1B	May damage fertility or the unborn child
Specific target organ toxicity – Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation)
Aspiration hazard Category 1	May be fatal if swallowed and enters airways

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) :

- Highly flammable liquid and vapor
- May be fatal if swallowed and enters airways
- Causes skin irritation
- May cause drowsiness or dizziness
- May damage fertility or the unborn child
- May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation)

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)

: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground/Bond container and receiving equipment.
Use explosion-proof electrical, lighting, ventilating equipment.
Do not breathe mist, spray, vapors.
Wash hands, forearms and face thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective clothing, eye protection, face protection, protective gloves.
If swallowed: Immediately call a poison center or doctor.
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If exposed or concerned: Get medical advice/attention.
Call a poison center or doctor if you feel unwell.
In case of fire: Use Dry chemical, CO₂, or water spray or regular foam to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Naphtha (petroleum), hydrotreated light	CAS-No.: 64742-49-0	30-50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
1-methoxy-2-propanol	CAS-No.: 107-98-2	10-20	Flam. Liq. 3, H226 STOT SE 3, H336
Toluene	CAS-No.: 108-88-3	10-20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Isobutyl isobutyrate	CAS-No.: 97-85-8	10-20	Flam. Liq. 3, H226 Aquatic Chronic 3, H412

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
2-Ethylhexanoic acid iron(2+) iron(3+) salt	CAS-No.: 68201-81-0	0.1-1	Acute Tox. 4 (Oral), H302 Repr. 1B, H360

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately. First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but not mouth-to-mouth.
First-aid measures after inhalation	: Call a physician immediately. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim is unconscious : Lay in a stable manner on victim's side. Induce artificial respiration with mask fitted with one-way valve or other suitable device; not mouth-to-mouth.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a physician immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Aspiration of the product into the lungs may cause very serious pneumonia. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Irritation (itching, redness, blistering). Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: Risk of lung edema. Risk of product entering the lungs on vomiting after ingestion.
Most Important Symptoms/Effects	: Risk of product entering the lungs on vomiting after ingestion.
Chronic symptoms	: May damage fertility or the unborn child. May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).

4.3. Immediate medical attention and special treatment, if necessary

IF exposed: Call a POISON CENTER or doctor/physician. Risk of product entering the lungs on vomiting after ingestion.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, or water spray or regular foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor. Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection. Large fires: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if it can be done without personal risk. Cool affected containers with flooding quantities of water. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all personal contact including breathing in the mist, spray, vapors. Do not take actions involving personal risks. Wear self-contained breathing apparatus. Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. No flames, no sparks. Eliminate all sources of ignition. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Evacuate the danger area. If outdoors, move to an area upwind of the danger area. Do not breathe mist, spray, vapors. Avoid contact with skin, eyes and clothing. No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. If possible without taking personal risks, remove ignition sources, ventilate area. Prevent other non-emergency personnel from entering the danger area.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate personnel to a safe area. Stop leak if safe to do so. Do not touch spilled material. Remove all sources of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.2. Environmental precautions

Do not let the product reach soil, drains, sewers, or surface and ground water.

6.3. Methods and material for containment and cleaning up

- For containment : Contain with non-combustible inert absorbent. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
- Methods for cleaning up : Take up in non-combustible inert absorbent and place into container for disposal. Contaminated absorbent material may pose the same hazard as the spilt product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Proper grounding procedures to avoid static electricity should be followed.

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Do not breathe mist, spray, vapors. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof equipment. Flammable vapors may accumulate in the container.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Store in a cool, dry and well-ventilated area away from incompatible substances. Use explosion-proof equipment.
Incompatible materials	: Strong oxidizers.
Packaging materials	: Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

FMI RC-21

No additional information available

2-Ethylhexanoic acid iron(2+) iron(3+) salt (68201-81-0)

No additional information available

Naphtha (petroleum), hydrotreated light (64742-49-0)

USA - ACGIH - Occupational Exposure Limits

Local name	Hexane (Commercial, <54% n-hexane)
ACGIH OEL TWA	100 ppm
Remark (ACGIH)	TLV® Basis: Periph neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024

1-methoxy-2-propanol (107-98-2)

No additional information available

Isobutyl isobutyrate (97-85-8)

No additional information available

Toluene (108-88-3)

USA - ACGIH - Occupational Exposure Limits

Local name	Toluene
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss. Notations: OTO; A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)

USA - ACGIH - Biological Exposure Indices

Local name	Toluene
BEI	0.3 mg/g Kreatinin Parameter: o-Cresol (with hydrolysis) - Medium: urine - Sampling time: End of shift - Notations: B 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Toluene
OSHA PEL TWA	200 ppm
OSHA PEL C	300 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation or process enclosure to keep the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Environmental exposure controls	: Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves. Wear suitable gloves resistant to chemical penetration

Eye protection:

Wear safety glasses which protect from splashes

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits

Personal protective equipment symbol(s):



FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Appearance	: Clear liquid.
Color	: Amber
Odor	: Sweet Solvent-like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.88
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Incompatible materials.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Naphtha (petroleum), hydrotreated light

LD50 oral rat	5000
LD50 dermal rat	2800 – 3100 mg/kg body weight
LC50 Inhalation - Rat	> 23.3 mg/l air

1-methoxy-2-propanol

LD50 oral rat	4016 mg/kg
LD50 oral	5900 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LD50 dermal	13000 mg/kg
LC50 Inhalation - Rat (Vapours)	27.3 mg/l/4h

Isobutyl isobutyrate

LD50 oral rat	> 2000 mg/kg body weight
LD50 dermal rabbit	> 8600 mg/kg
LC50 Inhalation - Rat	3.88 – 39.14 mg/l air

Toluene

LD50 oral rat	5580 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Toluene

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : May damage fertility or the unborn child.

Toluene

LOAEL (animal/female, F0/P)	520 mg/kg body weight (Development)
-----------------------------	-------------------------------------

STOT-single exposure : May cause drowsiness or dizziness.

1-methoxy-2-propanol

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Toluene

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-repeated exposure : May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).

Naphtha (petroleum), hydrotreated light	
LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air
NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air
1-methoxy-2-propanol	
LOAEL (oral, rat, 90 days)	2757 mg/kg body weight
NOAEL (oral, rat, 90 days)	919 mg/kg body weight
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg body weight
Toluene	
LOAEL (oral, rat, 90 days)	1250 mg/kg body weight
NOAEL (oral, rat, 90 days)	625 mg/kg body weight
NOAEC (inhalation, rat, vapor, 90 days)	2.355 mg/l air
STOT-repeated exposure	May cause damage to organs (central nervous system) through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : No data available

Naphtha (petroleum), hydrotreated light	
Viscosity, kinematic	0.67 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
1-methoxy-2-propanol	
Viscosity, kinematic	1.848 mm ² /s

Symptoms/effects after inhalation : Aspiration of the product into the lungs may cause very serious pneumonia. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

Symptoms/effects after skin contact : Irritation (itching, redness, blistering). Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : May cause slight irritation.

Symptoms/effects after ingestion : Risk of lung edema. Risk of product entering the lungs on vomiting after ingestion.

Most Important Symptoms/Effects : Risk of product entering the lungs on vomiting after ingestion.

Chronic symptoms : May damage fertility or the unborn child. May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Naphtha (petroleum), hydrotreated light	
LC50 - Fish [1]	8.2 mg/l
EC50 - Crustacea [1]	4.5 mg/l
LOEC (chronic)	0.32 mg/l
NOEC (chronic)	0.17 mg/l
NOEC chronic crustacea	2.6 mg/l
NOEC chronic algae	0.5 mg/l

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-methoxy-2-propanol	
LC50 - Fish [1]	≥ 1000 mg/l
EC50 - Crustacea [1]	21100 – 25900 mg/l
EC50 - Other aquatic organisms [1]	2954 mg/l
EC50 72h - Algae [1]	> 500 mg/l
Isobutyl isobutyrate	
LC50 - Fish [1]	14.22 mg/l
EC50 - Crustacea [1]	59.3 mg/l
LC50 - Fish [2]	12.5 mg/l
EC50 - Crustacea [2]	55.8 mg/l
EC50 72h - Algae [1]	23 mg/l
EC50 72h - Algae [2]	12 mg/l
Toluene	
LC50 - Fish [1]	5.5 mg/l
LOEC (chronic)	2.76 mg/l
NOEC (chronic)	0.74 mg/l
NOEC chronic fish	1.39 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

1-methoxy-2-propanol

Partition coefficient n-octanol/water (Log Pow)	-0.49
---	-------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations. Dispose of this material and its container at hazardous or special waste collection point. Refer to all applicable national, international and local regulations or provisions.
Additional information	: Flammable vapors may accumulate in the container. Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment.




FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
1268	1268	1268
14.2. Proper Shipping Name		
Petroleum distillates, n.o.s. (Naphtha (petroleum), hydrotreated light)	PETROLEUM DISTILLATES, N.O.S. (Naphtha (petroleum), hydrotreated light)	Petroleum distillates, n.o.s. (Naphtha (petroleum), hydrotreated light)
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

DOT

UN-No.(DOT)	: UN1268
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

IMDG

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Immiscible with water.

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 3H

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Naphtha (petroleum), hydrotreated light	CAS-No. 64742-49-0	30-50%
---	--------------------	--------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS-No. 108-88-3	10-20%
---------	------------------	--------

Toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

2-Ethylhexanoic acid iron(2+) iron(3+) salt (68201-81-0)

Listed on the Canadian NDSL (Non-Domestic Substances List)

1-methoxy-2-propanol (107-98-2)

Listed on the Canadian DSL (Domestic Substances List)

Isobutyl isobutyrate (97-85-8)

Listed on the Canadian DSL (Domestic Substances List)

Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

FMI RC-21

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

1-methoxy-2-propanol (107-98-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)


Isobutyl isobutyrate (97-85-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Toluene (108-88-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

 **WARNING:** This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.